



Mini-968/10Y

Carbon Monoxide Alarm, Photoelectric, 3V Sealed Battery

Key Information

Product brand:	Red Smoke Alarms
Product or component:	Carbon Monoxide Detector
Device application:	Early detection of carbon monoxide leakage
Electronic sensor type:	Electrochemical sensor
Colour:	White (RAL 9003)
Quantity per set:	Set of 1
Type of packing:	Carton

Complementary

Supply	3V DC Sealed Battery
Battery Type	Lithium Battery
Battery Life	10 Year
Operating Current	≤150mA at 3V
Standby Power	≤10mA
Detection Type	Carbon Monoxide
Function Available	Hush Function Self-test of CO detection Local alarm
Control Type	Button for test/ hush function
Alarm Response Time	50 PPM (60-90 mins) 100 PPM (10-40 mins) 300 PPM (<3 mins)
Noise Level	85 dB at 3m minimum
Time Delay Range	10 min for hush 10 hr for do not disturb
Local Signal	Sound : Alarm Sound : Signal Power Activation Signal (Green Light) Fault Warning (Yellow light flash 2 times) End of Life Signal (Yellow light flash 3 times) CO gas Warning Signal (Red Light)
Type of Installation	Indoor
Device Mounting	Surface
Mounting Support	Wall-mount
Fixing Mode	By screws
Dimension:	90 x 22 x 90 cm (L x W x H)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability of reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.

Neither Red Smoke Alarms PTY. LTD nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Ambient Air Temperature for Operation	0...50°C
Relative Humidity	5...95%
Standards	EN50291-1:2012+A1:2010
	Intertek Certificate No. 22302



SMOKE ALARMS

Data Sheet
Mini-968/10Y

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability of reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.

Neither Red Smoke Alarms PTY. LTD nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.